


Audio

Speaker cables, coaxial

HELUSOUND®



Type

Cable structure

Conductor material:
Core insulation:
Core colours:
Sheath material:
Cable external diameter:
Sheath colour:

Speaker cable

1x2,5

Copper, bare
PVC
Black
PVC
approx. 6,8 mm
Black

Speaker cable

1x4,0

Copper, bare
PVC
Black
PVC
approx. 7,9 mm
Black

Electrical data

Conductor resistance, max.:
Insulation resistance, min.:

7,98 Ohm/km
5 MOhm x km

4,95 Ohm/km
5 MOhm x km

Technical data

Weight:
Min. bending radius for laying:
Operating temperature range min.:
Operating temperature range max.:
Copper weight:

approx. 84 kg/km
68 mm
-25°C
+70°C
52,0 kg/km

approx. 129 kg/km
80 mm
-25°C
+70°C
87,0 kg/km

Norms

Halogen-free acc. to EN 50267-2-3

Halogen-free acc. to EN 50267-2-3

Part no.

400061

400062

Dimensions and specifications may be changed without prior notice.

Application

The coaxial HELUSOUND® speaker cable is protected by dual spiral screens in opposite directions and outer sheath. As well as robustness and good winding capability its design is particularly distinguished by high flexibility and small dimensions.